



MATERIALS:

	CENTER CONTACT	DIELECTRIC	SHELL
1- TYPE `N` MALE	Gold Plated Brass	Teflon	Silver Plated Brass
2- BNC MALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass
3- TNC MALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass
4- SMA MALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass
5- TYPE `N` FEMALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass
6- BNC FEMALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass
7- TNC FEMALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass
8- SMA FEMALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass
9- COUPLING ADAPTER	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass
10- DOUBLE BANANA PLUG	Spring: Beryllium copper ASTM B194, alloy 172 cond. Ht. Plug Body: Brass per QQ-B-626, alloy 360, 1/2 hard. Finish: Nickel plated per QQ-N-290, class2, 200/300 microinches Insulation: ABS. Color: Black Center Contact: Gold plated brass Dielectric: Teflon Shell: Silver plated brass		



All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ±.005" (.127 mm).
All specifications are to the latest revisions. Specifications are subject to change without notice.
Registered trademarks are the property of their respective companies. Made in USA

11- DOUBLE BINDING POST 	Body: Brass per QQ-B-626, alloy 360, 1/2 hard Finish: Nickel plated per QQ-N-290, class 2, 200/300 microinches Insulation: Polycarbonate. Color: one black, one red Insulation, Body: ABS. Color: Black Center Contact: Gold plated phosphor bronz Dielectric: Teflon Shell: Silver plated brass
---	---

	CENTER CONTACT	DIELECTRIC	SHELL
12- UHF MALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass
13- UHF FEMALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass
14- MINI UHF MALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass
15- MINI UHF FEMALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass
16- RCA PHONO MALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass
17- RCA PHONO FEMALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass
18- TYPE F MALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass
19- TYPE F FEMALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass
20- UNIDAPT SIGNAL SAMPLER	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass
21- LABEL, NOT SHOWN			
22- PLASTIC BOX W/ FOAMS			
23- PART CARD, NOT SHOWN			

RATING:

Operating Temp:

Items 1 through 9 and 12 through 20 : -67° F to +302° F (55° C to +150° C).

Items 10 and 11 : +122° F MAX. (+50° C MAX.)

Nomial Impedance:

Items 1 through 9 and 20: 50 Ohms.

Items 18 through 19: 75 Ohms.

Vswr Max.:

Items 1 through 9: 1.2: 1 (DC- 1GHz).

Items 12 through 15: 1.2: (DC- 300MHz).

Frequency Range:

Items 12 through 15: (500MHz MAX.)

Items 16 through 19: (DC to 300MHz).

Item 20: (50MHz to 3GHz).

Weight: 2.40 pounds.

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ±.005" (.127 mm).


All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies. Made in USA

6/9/99

SY/EH/LS

R:\Release\DataSheet3_Market_00\D5748_1_01.doc



P

M