



AU92 Automotive Multimeter

Model AU92 is a full featured multimeter that has additional measurement for automotive servicing. It offers a built-in thermometer to measure air, surface or immersion temperatures. The meter also tests engine RPM and dwell in addition to standard multimeter features of voltage, current, resistance and continuity. Perform accurate RPM measurements for 2- and 4-stroke automotive engines using the Inductive Pickup tool. A well designed tool for your automotive testing needs.

- Performs all standard electrical test for on-car and bench troubleshooting
- Tests engine RPM and dwell
- Capacitance, Frequency and Temperature
- Measures DC/AC voltage, DC/AC current, resistance, diodes and continuity beeper, duty cycle
- Accurate RPM measurements for 2- and 4-stroke automotive engines using the inductive probe
- Locate faulty wiring and components
- Data Hold button retains display data
- Protective holster with magnetic hanging strap
- Compact size
- Includes inductive pick-up probe, carrying case, test leads, test lead extender tips, threaded alligator clips, type k temperature probe, spare fuse



AU92

No hassle warranty

No waiting.

No shipping charges.



Our commitment to high-quality products and customer service is demonstrated by our industry exclusive "No Hassle" warranty. In the unlikely event that an Amprobe Test Tool requires warranty service, any of our local dealers are authorized to replace it, on the spot.

(note: \$500 MSLP limit)



AU92 Automotive Multimeter

Data Sheet

Specifications 23 °C ± 5 °C, < 75% R.H.

Function	Range	Accuracy
DC VOLTS		
	400 mV, 4 V, 40 V, 400 V, 600 V	±(1.0% rdg + 2 dgts)
Resolution:	0.1 mV	
Input impedance:	400 mV: >100 MΩ; 4 V:10 MΩ; 40 V ~ 600 V: 9.1 MΩ	
Overload protection:	600VDC or AC rms	
AC VOLTS		
	400 mV, 4 V, 40 V, 400 V, 600 V	
	400 mV (50 ~ 100 Hz)	±(2.0% rdg + 5 dgts)
	4, 40, 400, 600 V (50 ~ 500 Hz)	±(2.0% rdg + 5 dgts)
Resolution:	0.1 mV	
Input impedance:	400 mV: >100 MΩ; 4 V: 10 MΩ; 40 V ~ 600 V: 9.1 MΩ	
Overload protection:	600 VDC or AC rms	
DC CURRENT		
	400 μA, 4000 μA, 40 mA, 400 mA, 10 A	
	400 μA to 400 mA ranges	±(2.0% rdg + 2 dgts)
	10 A range	±(3.0% rdg + 3 dgts)
	10A input: 10 A for 60 seconds maximum followed by a 10 minutes cooling period	
Resolution:	0.1 μA	
Voltage burden:	0.2 V on 400uA, 40mA ranges 2V on 4000 uA, 400 mA ranges	
Input protection:	0.5 A / 500V fast blow ceramic fuse (FP520) 10 A / 500 V fast blow ceramic fuse (FP540)	
AC CURRENT (50-500 Hz)		
	400 uA, 4000 uA, 40 mA, 400 mA, 10 A	
	400 uA to 400 mA ranges	±(2.5% rdg + 5 dgts)
	10 A range	±(3.5% rdg + 5 dgts)
	10A input: 10 A for 60 seconds maximum followed by a 10 minutes cooling period	
Voltage burden:	see DC Current	
Input protection:	see DC Current	
RESISTANCE		
	400 Ω, 4 kΩ, 40 kΩ, 400 kΩ, 4 MΩ, 40 MΩ	
Resolution:	0.1 Ω on 400 Ω range	
	400 Ω to 400 kΩ ranges	±(1.5% rdg + 4 dgts)
	4 MΩ range	±(2.5% rdg + 4 dgts)
	40 MΩ range	±(5.0% rdg + 5 dgts)
Open circuit volts:	-0.45Vdc (-1.2Vdc on 400 Ω range)	
Overload protection:	600 VDC or AC RMS	
FREQUENCY (Hz) (Auto ranging)		
	4 kHz, 40 kHz, 400 kHz	
Resolution:	1Hz	±(0.1% rdg + 3 dgts)
Sensitivity:	10Hz ~ 400kHz: > 3.5Vrms	
Minimum pulse width:	> 2.5us	
Duty cycle limits:	>30% and < 70%	
Overload protection:	600 VDC or AC RMS	

Specifications, cont.

Function	Range	Accuracy
TEMPERATURE		
Ranges:	-20°C ~ 1000°C, -4°F ~ 1832°F	
Resolution:	0.1°C, 0.1°F	
	-20°C ~ 10°C	±(2.0% rdg + 4°C)
	10°C ~ 200°C	±(1.0% rdg + 3°C)
	-20°C ~ 10°C	±(2.0% rdg + 4°C)
	200°C ~ 1000°C	±(3.0% rdg + 2°C)
	-4°F ~ 50°F	±(2.0% rdg + 8°F)
	50°F ~ 400°F	±(1.0% rdg + 6°F)
	400°F ~ 1832°F	±(3.0% rdg + 4°F)
Sensor type:	K-type thermocouple	
Overload protection:	600 VDC or AC RMS	
RPM		
Range: RPM	600 ~ 4000 RPM	
X10 RPM	4000 ~ 12000 RPM	
Resolution:	1 RPM	±(2% rdg + 4 dgts)
Effect Reading:	> 600 RPM	
Overload protection:	600 VDC or AC RMS	
% DUTY CYCLE		
	1.0% ~ 90.0%	
Resolution:	0.1%	
Pulse width:	> 100us, < 100ms	±(2% rdg + 5 dgts)
Overload protection:	600 VDC or AC RMS	
DWELL ANGLE		
No. of Cylinders: 4, 5, 6, 8		
	4 CYL	0 ~ 90.0°
	5 CYL	0 ~ 72.0°
	6 CYL	0 ~ 60.0°
	8 CYL	0 ~ 45.0°
Resolution:	0.1°	±(2% rdg + 5 dgts)
Overload protection:	600 VDC or AC RMS	
CONTINUITY		
Audible indication:	Less than 25Ω	
Response time:	500ms	
Overload protection:	600VDC or AC RMS	
DIODE TEST		
Test current:	1.0mA (approximate)	±(3.0% rdg + 3 dgts)
Resolution:	10mV	
Audible indication:	<0.25V	
Open circuit volts:	3.0VDC typical	
Overload protection:	600VDC or AC RMS	

AU92 Automotive Multimeter

Data Sheet

Included Accessories

One pair test leads, temperature adapter, inductive pick-up probe, Type-K thermocouple, One spare fuse (0.5A/500V), 9V battery (installed), carrying case and users manual.



General Specifications

Display: 3¾ digit liquid crystal display (LCD) with a maximum reading of 3999.

Polarity: Automatic, positive implied, negative polarity indication.

Overrange: (OL) or (-OL) is displayed.

Zero: Automatic.

Low battery indication: The "⚡" is displayed when the battery voltage drops below the operating level.

Measurement rate: 2 times per second, nominal.

Auto power off: Approx. 10 minutes.

Operating environment: 0°C to 50°C at < 70% RH.

Storage temperature: -20°C to 60°C at < 80% RH.

Accuracy: Stated accuracy at 23°C ± 5°C, <75% RH.

Temperature Coefficient: 0.1 × (specified accuracy) per °C. (0°C to 18°C, 28°C to 50°C).

Altitude: 2000m, indoor operation

Power: Standard 9-volt battery, NEDA 1604, JIS 006P, IEC 6F22.

Battery life: 150 hours typical with carbon zinc.

Dimensions: 165 × 78 × 50 mm (6.5 × 3.1 × 1.9 in.)

Weight: Approx. 315g (11.1 oz.) including holster.

CE Safety: Meets IEC61010-1 2nd Ed., UL61010-1 2nd Ed. CAT III-600 Volts AC & DC; Class II; Pollution degree: 2; EN61010-2-032

EMC: Conforms to EN61326-1.