

## Portable Spectrum Analyzer



- ✓ **Small Compact Design**
- ✓ **Battery Powered for Remote Field Use**
- ✓ **13/18 Volt LNB Power & 22KHz**
- ✓ **4 R.B.W. Selections including 10KHz**
- ✓ **Ethernet & Serial Communications**
- ✓ **User Friendly and Intuitive GUI**

## PSA-2150C

### Technical Specifications

Frequency Coverage:	950MHz – 2,150 MHz
Span Width:	0 - 1300 MHz
Resolution Bandwidth:	10KHz, 100KHz, 300KHz, 1MHz
RF Sensitivity:	Greater than - 85 dBm Typical
Reference Levels:	Selectable - 10 dBm, - 30 dBm, -50 dBm
Scale:	5 dB & 2dB per Division
Dynamic Range:	40 dB on Application Window
Amplitude Accuracy:	+/- 1 dB typical
Frequency Accuracy:	+/- 1KHz typical
Input Connector:	"BNC" is standard "F", "N", "SMA" & "TNC" available
Inputs:	Single is Standard, Dual Available
Size:	9.25" W x 6" H x 7" D
Weight	6 Lbs.
Power Requirements:	+15 VDC
Display:	Full VGA Color LCD

Note: Specifications are based on Avcom control system and graphical user interface and may vary depending on the control system used. Please contact for specifications based on the selected platform.

Specifications subject to change  
PSA-2150C

### Small Compact Design

The PSA-2150C was designed for the Field Engineer to have a very useful, compact tool that eliminates the need for carrying around a big bulky bench-top unit. The PSA-2150C has the option to have dual switching inputs so that you can easily setup cross pole or monitor 2 different feeds simultaneously.

### Improved Performance & Specifications

The new PSA-2150C was designed for excellent frequency and amplitude accuracy with a wide variety of resolution bandwidth selections ranging from 10KHz to 1MHz. This is required to allow for viewing and monitoring of small TT&C and data carriers found in many satellite communications markets today. The wideband input will also allow for monitoring of a 10MHz reference signal as well.

### Versatile Graphical User Interface

The new Avcom Graphical User interface (GUI) is based on the National Instruments Labview Platform and has been customized for several of our customer's applications. The Avcom GUI will run on the WINDOWS 2000, XP and Vista platforms. Avcom also offers a multi user version of the software so that multiple users can monitor at the same time. Please contact Avcom for any questions regarding the GUI or if you wish to use your own software with this product.

