

SPECIFICATIONS

1504

DESCRIPTION: 0-12VDC, 500mA Power Supply
INPUT VOLTAGE: 120VAC, 60Hz
ENVIRONMENTAL TEMPERATURE: 25°C

0-12VDC:	Min.	Max.
Output Voltage Range	0.1V	12V
Minimum Output Voltage		100mV
Maximum Output Voltage	12V	13.5V
Output Current	0.4A, typical	

VOLTAGE REGULATION:

Load (0-100% load)	400mV
Line (100-130VAC Variation)	200mV
Ripple & Noise	100mVp-p

12VAC:		
Output Voltage No Load	12.5V	15V
Output Voltage Full Load	11.5V	
Output Current	0.5A, typical	

No Load Input current		50mA
Full Load Input Current (All rated load)		200mA
Fuse 1	1A, typical	
Fuse 2	0.5A, typical	

Dimensions (W X D X H): 101 mm x 140 mm x 83 mm

Weight: 0.90 kgs

Description:

This power supply gives you two outputs, 12VAC and a 0-12VDC. By offering two different outputs you can choose from either AC voltage or DC voltage.

Operation:

Plug model 1504 into an AC outlet. Turn power switch on. Adjust voltage with control knob. Connect to either 12VAC (constant) or 12VDC (variable).