

## 600A AC/DC Clamp+MultiMeter

Autoranging pocket size clamp-on in rugged housing

### Features:

- Large 2400 count display (4999 counts for Hz)
- Clamp jaws open to 1.2" (30mm), 350MCM
- Compact, rugged clamp-on with splash resistant front panel design
- Measure AC/DC Current and Voltage, Frequency and Resistance
- Auto or manual ranging with Data Hold and Relative mode
- Continuity beeper and Diode test
- Overload protection on all ranges
- Complete with test leads, two 1.5V AA batteries and carrying case



CAT II-600V

Specifications	Range	Max. Resolution	Basic Accuracy (%rdg+digits)
AC Current:	600A	0.1A	±(2% + 5d)
DC Current:	600A	0.1A	±(2% + 8d)
AC Voltage:	600V	0.001V	±(1.2% + 5d)
DC Voltage:	600V	0.1mV	±(1% + 2d)
Resistance:	24MΩ	0.1Ω	±(1% + 5d)
Frequency:	100kHz	0.01Hz	±(1% + 5d)
Continuity:	<10Ω, beeper will sound		
Diode test:	yes		
Power:	two 1.5V AA Batteries		
Dimensions:	7.0 x 2.5 x 1.3" (178 x 64 x 33mm)		
Weight:	8oz (230g)		



### Ordering Information:

- 38394** .....600A AC/DC Clamp+MultiMeter  
**38394-NIST** .....600A AC/DC Clamp+MultiMeter with NIST Certificate  
**480172** .....AC Line Separator  
**381277** .....Temperature Adaptor, K probe