

Flat Surface Stem Dial Thermometer

Model 392052

Specifications

Display	2000 count liquid crystal display
Units	°C/°F selectable
Measurement range	-58 to 572°F (-50 to 300°C)
Resolution	0.1° to 199.9°, 1° > 199.9°
Accuracy	±1.8°F (1°C) from -22 to 452°F (-30 to 250°C) : ±4°F (2°C) outside this range
Sensor length	5" (130mm)
Sensor tip diameter	0.57" (14.5mm)
Sensor material	Stainless steel
Auto Off	After one hour of operation
Operating temperature for display	14 to 122°F (-10 to 50°C) (dial display)
Battery	one 1.5V LR44 cell or equivalent (A76/G13) cell

Operation

Battery Installation/Replacement

Using a coin or a screwdriver, turn the battery compartment cover a quarter turn to the left. Remove the cover and install/replace the battery observing the proper polarity.

Taking Temperature Measurements

1. Slide the ON/OFF switch to turn the thermometer on. The digital display will begin to indicate temperature. If the display does not operate, replace the battery.
2. Slide the °F/C button to select the desired temperature units.
3. Place the sensor disk flat against the surface to be measured and read the temperature on the display.

Considerations

- For best results, the probe disk should be held flat against the surface and the surface should be free of any dirt or substance that will inhibit thermal contact.
- The thermometer should not be placed inside any oven or microwave.
- Remove the battery from the thermometer if it is not to be used for an extended time period.