

ExStik® Waterproof Refillable pH Meter

Features flat surface electrode, RENEW and CALibration alerts, memory, and bargraph
Indicator tells you it's time to replace your electrode and eliminates guesswork

Features:

- ✓ Refillable pH electrode is easily serviced. Fresh reference solution maintains high accuracy. Eliminates concern with shelf life.
- ✓ Flat Surface Electrode measures pH in liquids, semi-solids, and solids. No more electrode breakage or clogged junctions.
- ✓ CAL alerts tells you it's time to recalibrate. Ensures accuracy.
- ✓ Memory records and recalls 15 sequentially tagged readings. Allows detection of changes over time.
- Analog bargraph displayed on LCD. Shows trends in acidity or alkalinity.
- 1, 2 or 3 point calibration automatically recognizes buffer solutions
- Automatic Temperature Compensation
- Simultaneous display of pH and Temperature
- Waterproof to IP57 standard
- Display indicates when the reading is stabilized
- Data Hold, Auto power off and low battery indication
- Waterproof design floats in water and protects the meter in wet environment
- Interchangeable probes available for Chlorine & ORP
- Optional weighted base (EX006) holds plastic cup and ExStik® meter
- Complete with refillable flat surface pH electrode, 1.5mL bottle KCl, 2 reference junctions, 2 removal tools, protective sensor cap, sample cup with cap, four 3V CR-2032 button batteries, and 48" (1.2m) neckstrap

Test Equipment Depot
1-800-517-8431

99 Washington Street
Melrose, MA 02176
Phone 781-665-1400
Toll Free 1-800-517-8431

Visit us at www.TestEquipmentDepot.com
Back to the Extech PH110 Product Info Page



Model PH113 Reference Refill Solution Kit includes:

- 1.5mL bottle KCl,
- 2 reference junctions and
- 2 removal tools.



Specifications

pH	0.00 to 14.00pH
Temperature	23 to 194°F (-5 to 90°C)
Resolution	0.01pH, 0.1°
Accuracy	±0.01pH, ±1.8°F/±1°C
Power	four LR44 button batteries
Dimensions	1.4 x 6.8 x 1.6" (35.6 x 172.7 x 40.6mm)
Weight	3.8oz (110g)

