

© SPECIFICATION (MODEL : DM-531, DM-532)

FUNCTION	RANGE	RESOLUTION	ACCURACY
DC VOLTAGE	400mV	0.1mV	± 0.5 % of READING ± 5 DIGIT
	4V	0.001V	
	40V	0.01V	
	400V	0.1V	
	1000V	1V	± 1.0 % of READING ± 5 DIGIT
AC VOLTAGE	400mV	0.1mV	± 1.2 % of READING ± 5 DIGIT 40Hz ~ 400Hz
	4V	0.001V	
	40V	0.01V	
	400V	0.1V	
	750V	1V	± 2 % of READING ± 5 DIGIT 40Hz ~ 400Hz
DC AMPERE	400uA	0.1uA	± 1 % READING ± 5 DIGIT
	4000uA	1uA	
	40mA	0.01mA	
	400mA	0.1mA	
	10A	0.01A	

AC AMPERE	400uA	0.1uA	±2 % READING ±5 DIGIT 40Hz ~ 400Hz
	4000uA	1uA	
	40mA	0.01mA	
	400mA	0.1mA	
	10A	0.01A	
OHMS	400.0 Ω	0.1 Ω	±1.0 % READING ±5 DIGIT
	4.000k Ω	0.001k Ω	
	40.00k Ω	0.01k Ω	
	400.0k Ω	0.1k Ω	±1.5 % READING ±5 DIGIT
	4.000M Ω	0.001M Ω	
	40.00M Ω	0.01M Ω	
CONTINUITY	35 Ω		
DIODE CHECK	1V 2mA		
FREQUENCY	40Hz ~ 400MHz		±0.5 % READING ± 5 DIGIT
CAPACITANCE	40nF ~ 400uF		±2 % READING ± 40 DIGIT
	400uF ~ 4mF		±6 % READING ± 40 DIGIT
VOLT/FREQ (V-Hz)	40Hz ~ 1MHz		±0.5 % READING ± 3 DIGIT