

SecuriTEST™ CCTV/Security Tester



- **Six Essential CCTV Tools** – Combines a CCTV video tester, PTZ camera controller, Digital Multi-Meter, UTP cable tester, video test pattern generator and PTZ protocol analyzer in a single compact package.
- **Save Time & Money** – Test, aim and focus cameras when working alone and save time by not having to walk back to the control center to verify functionality of each camera.
- **Compact Design** – Combines all the most needed—security tools in a lightweight, easy-to-carry unit with a sharp, bright 2.5in (6.3cm) color LCD screen with on-screen displays for PTZ control/diagnostics and DMM readouts.
- **PTZ Protocol Analyzer** – Compatible with over a dozen PTZ protocols to test and program cameras in the field. Decodes and identifies output from PTZ console to aid in troubleshooting.

SecuriTEST is the most versatile all-in-one installation and troubleshooting tool for the CCTV professional.

CCTV installers often need to carry a variety of testing tools to complete their work. SecuriTEST combines the most-needed tools in one easy-to-carry package. Since all connections (video/communications/DMM) attach to a single unit, SecuriTEST eliminates the need to juggle several devices while on a ladder or lift, making working conditions safer and increasing productivity.





No. 33-891

SPECIFICATIONS		
Electronics	Input Voltage	12VDC +/- 10%, 1A
	Battery	6 AA Alkaline or NiMH
	Internal Charger	Charging Time 6+ Hrs Operating Time 4 Hrs
Video	Signal Format	NTSC or PAL
	Video Level	1Vpp, 140IRE
PTZ Control	Supported Protocols	Multi-protocol support including: Panasonic, Samsung, Pelco D/P, WonWoo, FASTRACK, WV-CS850, and more
	Baud Rates	2400-38400bps
	Data Communications	RS-422 or RS-485
UTP Cable Test	Detects	Straight/cross cables, open, short, miswire, split pairs
Multimeter	AC/DC Voltage	400V
	AC/DC Current	4mA, 400mA, 10A
	Resistance	40Mohm
Fuse	250V, 800mA	

DESCRIPTION	CAT NUMBER
SecuriTEST CCTV/Security Tester	33-891

SecuriTEST

Catalog No. 33-891

- SecuriTEST Handheld Tester
- 6 AA Batteries
- AC Adapter/charger (110-240V input)
- 4ft (1.2m) BNC video cable
- DMM test leads
- UTP cable terminator
- Neck strap

Dimensions

- Length: 2.3in (5.8cm)
- Width: 3.5in (8.8cm)
- Height: 7.5in (19.0cm)
- Weight: 0.86lbs (390g)

RS-422/485 In/Out

BNC Video Input

BNC Video Output



UTP Test Port

Aux Input

Power Input



LED Indicators

Main Power Switch

PTZ Control Pad

Test Lead Ports