

Function Generator



GFG-8255A (5MHz)



GFG-8250A (5MHz)

FEATURES

- * Frequency Range: 0.5Hz ~ 5MHz
- * Waveforms: Sine, Triangle, Square, Ramp, TTL and CMOS Output
- * External Voltage Controlled Frequency (VCF) Function
- * Duty Cycle Control with Signal Inversion Capability
- * Variable DC Offset Control
- * Two-Step (-20dBx2) and Variable Attenuator
- * Built-in 6 Digit Counter with INT/EXT Function Up to 150MHz / High Resolution
- * INT/EXT AM/FM Modulation (GFG-8255A)
- * GCV Output for Synchronization (GFG-8255A)
- * LIN/LOG Sweep Mode (GFG-8255A)

SPECIFICATIONS

MAIN	
Frequency Range	0.5Hz ~ 5MHz (7 Range)
Amplitude	> 10Vpp (into 50Ω load)
Impedance	50Ω ± 10%
Attenuator	-20dB ± 1dBx2
DC Offset	<-5V ~ >5V (into 50Ω load)
Duty Control	80% : 20% : 80% to 1MHz Continue variable
Display	6 digit LED display
SINE WAVE	
Distortion	≤ 1%, 0.5Hz ~ 100kHz
Flatness	≤ 0.3dB, below 500kHz ≤ 1dB, below 5MHz
TRIANGLE WAVE	
Linear	≥ 98%, 0.5Hz ~ 100kHz ≥ 95%, 100kHz ~ 5MHz
SQUARE WAVE	
Symmetry	± 2%, 1Hz ~ 100kHz
Rise or Fall Time	≤ 50nS at maximum output (into 50Ω load)
CMOS OUTPUT	
Level	4Vpp ± 1Vpp ~ 14.5Vpp ± 0.5Vpp adjustable
Rise or Fall Time	≤ 120nS
TTL OUTPUT	
Level	≥ 3Vpp
Fan Out	20 TTL load
Rise or Fall Time	≤ 25nS
VCF	
Input Voltage	0V ~ 10V ± 1V (100 : 1)
Input Impedance	10kΩ ± 10%
GCV(FOR GFG-8255A ONLY)	
Output Voltage	To set the voltage between 0V ~ 2V as per different frequency
SWEEP OPERATION (FOR GFG-8255A ONLY)	
Sweep/Manual	Switch selector
Sweep/Rate	100 : 1 ratio max. and adjustable
Sweep/Time	0.5sec. ~ 30sec. adjustable
Sweep/Mode	Lin./Log. switch selector
AMPLITUDE MODULATION (FOR GFG-8255A ONLY)	
Depth	0 ~ 100%
MOD. Frequency	400Hz (INT), DC ~ 1MHz(EXT.)
Carrier BW	100Hz ~ 5MHz (-3dB)
EXT Sensitivity	< 10Vpp for 100% modulation

FREQUENCY MODULATION (FOR GFG-8255A ONLY)

Deviation	0 ~ ± 5%
MOD. Frequency	400Hz (INT), DC ~ 20kHz(EXT.)
EXT. Sensitivity	≤ 10Vpp for 10% modulation

FREQUENCY COUNTER

INT./EXT.	Switch selector
Range	0.5Hz ~ 5MHz (5Hz ~ 150MHz EXT.)
Accuracy	Time base accuracy ± 1 count
Time Base	± 20ppm (23°C ± 5°C) after 30 minutes warm up
Resolution	The maximum resolution is 100nHz for 1Hz and 1Hz for 100MHz
Input Impedance	1MΩ // 150pF
Sensitivity	≤ 35mVrms (5Hz ~ 100MHz) ; ≤ 45mVrms (100MHz ~ 150MHz)

POWER SOURCE

AC115V/230V ± 15%, 50/60Hz

ACCESSORIES

Instruction manual x 1, Power cord x 1, GTL-101 x 2

DIMENSIONS & WEIGHT

251(W) x 91(H) x 291(D)mm, Approx. 2.4kg

ORDERING INFORMATION

GFG-8255A	5MHz Function Generator with Lin/Log Sweep, GCV Function, AM/FM Modulation
GFG-8250A	5MHz Function Generator