

# Model CT231A

## Amp Clamp Accessory



### CT231A Specifications (at 23 °C ± 5 °C, < 75 % R.H. non-condensing)

#### AC Current (50-1000 Hz)

Range	1 to 200 A
Accuracy	Meter impedance (Load = 1 Ω max.): 1 A to 40 A: ± (3 % rdg + 0.5 A) 40 A to 200 A: ± (2 % rdg + 0.5 A)
	Meter impedance (Load = 10 Ω max.): 1 to 200 A: ± (3.0 % rdg + 0.15 A)

Division Ratio	1000 to 1
Output	1 A at jaws = 1 mA to meter

#### Overload Protection

Max Operating Voltage	600 V rms
-----------------------	-----------



### General Specifications

**Max Conductor Diameter:** 20 mm (0.78"); **Dimensions:** 30 x 51 x 139 mm (1.2" x 2.0" x 5.5"); **Lead Length:** 1.5 m (59"); **Operating Temperature:** - 10 °C to + 50 °C; **Dimensions (HxWxD):** 30 x 51 x 139 mm (1.2" x 2.0" x 5.5"); **Weight:** 260 grams (9 oz); **Included Accessories:** Operators manual

#### Features

Permanently Attached Leads; Warranty: One-year

#### Optional Accessories

VC30 Vinyl Case

For additional accessories, see the Accessories Compatibility Guide at [www.metermantesttools.com](http://www.metermantesttools.com)



- AC current clamp, 200 A
- CAT III 600 V rated

Test Equipment Depot  
99 Washington Street  
Melrose, MA 02176-6024

[www.testequipmentdepot.com](http://www.testequipmentdepot.com)  
800-517-8431  
781-665-0780 FAX