

Mi404/Mi406/Mi413/Mi414

Free & Total Chlorine and Chloride Photometers

Milwaukee provides a range of chlorine photometers for all applications: swimming pool treatments, household cleaners, dishwasher additives, laundry powders/liquids and cooling water treatment products all contain chlorine as an oxidizing biocide. Drinking water contains residual chlorine to maintain water purity throughout the supply lines.

Milwaukee offers 3 microprocessor-based instruments with greater resolution, better accuracy and immediate results. You can choose between three different models: Mi404 for measuring free (0.00 to 5.00 mg/L) and total (0.00 to 5.00 mg/L) chlorine, Mi406 for measuring free (0.00 to 5.00 mg/L) chlorine and Mi413 for measuring free (0.00 to 10.00 mg/L) and total (0.00 to 10.00 mg/L) chlorine.

Chloride is a major constituent of sea water and is extremely corrosive in acidic environments. It requires close monitoring in applications such as marine boiler systems that are effected by seawater contamination. Chlorides are used by the water treatment professional to determine cycles of concentration in low pressure boilers and cooling systems. It is essential to monitor chloride concentrations in boiler systems to prevent metal parts being damaged. In high levels, chloride can corrode stainless steel.



Specifications		 Mi404 <i>Free & Total Chlorine</i>	 Mi406 <i>Free Chlorine</i>	 Mi413 <i>Free & Total Chlorine HR</i>	 Mi414 <i>Chloride</i>
Range	Free Chlorine Total Chlorine Chloride	0.00 to 5.00 mg/L Cl ₂ 0.00 to 5.00 mg/L Cl ₂	0.00 to 5.00 mg/L Cl ₂	0.00 to 10.00 mg/L Cl ₂ 0.00 to 10.00 mg/L Cl ₂	0.00 to 20.00 mg/L Cl ⁻
Resolution	Free Chlorine Total Chlorine Chloride	0.01 mg/L (0.00 to 3.50 mg/L); 0.10 mg/L (above 3.50 mg/L); 0.01 mg/L (0.00 to 3.50 mg/L); 0.10 mg/L (above 3.50 mg/L)	0.01 mg/L (0.00 to 3.50 mg/L); 0.10 mg/L (above 3.50 mg/L)	0.01 mg/L (0.00 to 3.50 mg/L); 0.10 mg/L (above 3.50 mg/L); 0.01 mg/L (0.00 to 3.50 mg/L); 0.10 mg/L (above 3.50 mg/L)	0.01 mg/L
Accuracy	Free Chlorine Total Chlorine Chloride	±0.04 mg/L @1.50 mg/L ±0.04 mg/L @1.50 mg/L	±0.04 mg/L @1.50 mg/L	±0.10 mg/L @5.00 mg/L ±0.10 mg/L @5.00 mg/L	±0.4 mg/L @10.0 mg/L
Method		adaptation of the USEPA method 330.5 and Standard Method 4500-Cl G	adaptation of the USEPA method 330.5 and Standard Method 4500-Cl G.	adaptation of the USEPA method 330.5 and Standard Method 4500-Cl G.	adaptation of mercury (II) thiocyanate method
Light Source		tungsten lamp	tungsten lamp	tungsten lamp	Blue LED 466 nm
Light Detector		silicon photocell and 525 nm narrow band interference filter	silicon photocell and 525 nm narrow band interference filter	silicon photocell and 525 nm narrow band interference filter	silicon photocell and 466 nm narrow band interference filter
Environment		0 to 50°C / 32 to 122°F; max RH 100%	0 to 50°C / 32 to 122°F; max RH 100%	0 to 50°C / 32 to 122°F; max RH 100%	0 to 50°C / 32 to 122°F; max RH 100%
Battery Type		1 x 9V	1 x 9V	1 x 9V	1 x 9V
Auto-off		after 10 minutes of non-use	after 10 minutes of non-use	after 10 minutes of non-use	after 10 minutes of non-use
Dimensions		192 x 104 x 52 mm	192 x 104 x 52 mm	192 x 104 x 52 mm	192 x 104 x 52 mm
Weight		380 g	380 g	380 g	380 g

Accessories

- Mi504-100 Free & Total Chlorine reagent set (100 tests)
- Mi506-100 Free Chlorine reagent set (100 tests)
- Mi513-045 Free & Total Chlorine reagent set (45 tests)
- Mi514-100 Chloride reagent set (100 tests)

- Mi0001 Glass cuvetts (2 pcs)
- Mi0002 Caps for cuvetts (2 pcs)
- Mi0003 Stoppers for cuvetts (2 pcs)
- Mi0004 Tissue for wiping cuvetts (4 pcs)
- Mi0005 9V battery (1 pc)



Ordering Information

Mi404, Mi413 and Mi414 are supplied complete with 2 cuvetts, reagents, hard carrying case, wiping tissue, 9V battery and instructions.