

# Mi405/Mi407/Mi408/Mi412

## Ammonia, Iron & Phosphate Photometers



These user-friendly Colorimeters will give you direct readings in mg/L.

Ammonia detection in water treatment systems is particularly important for aquarium owners and fish farm operators. Ammonia is highly soluble in water and extremely toxic to fish. Fish farm owners must monitor and maintain careful control of ammonia levels to ensure optimum water conditions for their stock.

Milwaukee offers 2 instruments for low and medium concentrations: Mi405 with a range of 0.00 to 9.99 mg/L and Mi407 from 0.00 to 3.00 mg/L



Iron is naturally present in water supplies and its presence in both potable and industrial applications is regarded as objectionable. Milwaukee offers Mi408 Iron meter with a range of 0.00 to 5.00 mg/L.

Phosphates are present in natural waters and at concentrations typically found, do not pose any specific health threats to humans.

However, excessive contamination of water courses from agricultural fertilizer run off or wastewater/effluent discharge can promote excessive algae or plant growth.

Milwaukee offers Mi412 with range 0.00 to 2.50 mg/L.

### Specifications

		 <b>Mi405</b> <b>Ammonia MR</b>	 <b>Mi407</b> <b>Ammonia LR</b>	 <b>Mi408</b> <b>Iron HR</b>	 <b>Mi412</b> <b>Phosphate LR</b>
Range	Ammonia Iron Phosphate	0.00 to 9.99 mg/L (NH <sub>3</sub> -N)	0.00 to 3.00 mg/L (NH <sub>3</sub> -N)	0.00 to 5.00 mg/L Fe	0.00 to 2.50 mg/L PO <sub>4</sub>
Resolution	Ammonia Iron Phosphate	0.01 mg/L	0.01 mg/L	0.01 mg/L	0.01 mg/L
Accuracy	Ammonia Iron Phosphate	±0.10 mg/L @5.00 mg/L	±0.04 mg/L @1.50 mg/L	±0.03 mg/L @1.50 mg/L	±0.04 mg/L @1.00 mg/L
Method		adaptation of Nessler method	adaptation of Nessler method	adaptation of the USEPA method 315 B and Standard method 3500 - Fe B	adaptation of Ascorbic Acid method
Light Source		Blue LED 466 nm	Blue LED 466 nm	tungsten lamp	tungsten lamp
Light Detector		silicon photocell and 466 nm narrow band interference filter	silicon photocell and 466 nm narrow band interference filter	silicon photocell and 525 nm narrow band interference filter	silicon photocell and 610 nm narrow band interference filter
Environment		0 to 50°C / 32 to 122°F; max RH 100%	0 to 50°C / 32 to 122°F; max RH 100%	0 to 50°C / 32 to 122°F; max RH 100%	0 to 50°C / 32 to 122°F; max RH 100%
Battery Type		1 x 9 volt	1 x 9 volt	1 x 9 volt	1 x 9 volt
Auto-off		after 10 minutes of non-use	after 10 minutes of non-use	after 10 minutes of non-use	after 10 minutes of non-use
Dimensions		192 x 104 x 52 mm	192 x 104 x 52 mm	192 x 104 x 52 mm	192 x 104 x 52 mm
Weight		380 g	380 g	380 g	380 g

### Accessories

- Mi512-100 Phosphate LR reagent (100 tests)
- Mi508-100 Iron HR reagent (100 tests)
- Mi507-100 Ammonia LR reagent (100 tests)
- Mi505-100 Ammonia MR reagent (100 tests)

- Mi0001 Glass cuvettes (2 pcs)
- Mi0002 Caps for cuvettes (2 pcs)
- Mi0003 Stoppers for cuvettes (2 pcs)
- Mi0004 Tissue for wiping cuvettes (4 pcs)
- Mi0005 9V battery (1 pc)



### Ordering Information

Mi405, Mi407, Mi408 and Mi412 are supplied complete with 2 cuvettes, reagents for 100 tests, hard carrying case, wiping tissue, 9V battery and instructions.