

CE



SM700 Portable Lux Meter

The light is necessary for the development of the plants. In fact, it is necessary a sufficient contribution of light in order to favor the photosynthesis and the closing of the plants.

The supplement of light by means of lamps electrical workers is the method simpler and economic in order to bring the necessary light to the plants.

SM700 is a portable Lux meter designed to perform light measurements. It is supplied with a light sensor connected to the meter that measures from 0 to 50000 Lux.

Average indoor lighting ranges from 100 to 1000 Lux and average outdoor sun lights about 50000 Lux. Lux is a unit that indicates the density of light that falls on a surface.

The human eye is sensitive only to blue, green, and red light, so in calculating the Lux falling on an object, only the light that the human eye sees is counted. When only infrared light falls on an object, the Lux is counted as zero since our eyes see nothing. Mathematically, a spectral weighting function becomes convolved with the actual illumination spectrum to calculate Lux exactly.

This is the formal definition of Lux and it makes Lux an unusual unit of measure.



Still, Lux can be thought of as a way of measuring light in terms of what our eyes perceive. The metric unit of measure for luminance of a surface. One Lux is equal to one Lumen per square meter. One Lux equals 0.0929 footcandles.

Specifications	SM700
Range	0.000 to 1999 Lux 2000 to 19999 Lux 20000 to 50000 Lux
Range setting	manual through key buttons
Resolution	1 Lux 10 Lux 100 Lux
Accuracy	±6% of reading ±1 digit
Peak Wave Length	560 nm
Sensor Type	silicon photodiode
Sensor Sensitivity	100 scotopic Lux
Sensor Stability	±2% change per year (in the first two years)
Environment	0 to 50°C / 32 to 122°F; max RH 95%
Battery Type	1 x 9V (IEC 6LR61) alkaline
Battery Life	approximately 150 hours of continuous use
Auto-off	after about 5 minutes of non-use
Weight	approximately 270 g (meter with sensor)

Ordering Information

SM700 is supplied complete with 9V battery and instructions.



Light Sensor

SM700 is provided with a light sensor connected to the meter through a coaxial cable.

Range keys

Press one of the three "Range keys" to select the proper scale according to the intensity of the light.

