

<b>MSD600-Series</b>			
	MSD600C-III PT0600C-III (1)	MSD600C-5.1 PT0600C-5.1 (1)	MSD600M /SA (2)
<b>Display:</b>			
Display Type	LCD	LCD	LCD
Colour/Mono	Color	Color	Color
Display View Area, mm	135x100		
Display Resolution	640x480 VGA		
<b>Interface:</b>			
Analog Stereo Inputs (3)	1	-	1-4 (4)
Analog Stereo Outputs	1	-	1-4 (4)
Digital AES/EBU Inputs	2	3	1-16 (4)
Digital AES/EBU Outputs	2	-	1-4 (4)
LED Overload	-	-	-
Audio Connectors	DSUB	DSUB	DSUB
<b>Analyzer:</b>			
Phasemeter	+	+	+
Audio Vector Oscilloscope	+	+	+
PPM/VU Level Meter Scales (5)	7	7	7
Loudness (Leq (m))	+	+	+
Session Log	-	-	+
Statistical Info Mode	-	-	-
FFT Spectrum Analyzer	+	+	+
1/3 Octave Spectrum Analyser	+	+	+
Surround Sound "Jelly-Fish"	+	+	+
Signal Generator	+	-	+(6)
<b>Miscellaneous:</b>			
Presets	+	+	+
I/O Interface Module Option	-	-	+
VGA Output	+	+	+
Supply Voltage Range	12-24 V DC		
Dimensions mm (HxWxD)	144x186x36 (133x214x41)		133x186x50

(1) MSD600C-III and MSD600C-5.1 is a standalone versions. PT0600C-III and PT0600C-5.1 is a rack-mounted versions of the same units.

(2) Module based. Each unit can be outfitted with up to 4 input/output moduls.

(3) Balanced Analog Input circuit.

(4) Modules currently available for the MSD600M:

MSD600-Input/1 1 Stereo Analog Input + 1 Digital AES Input

MSD600-Input-2D/0 2 Digital AES Inputs.

MSD600-Input-4D/0 4 Digital AES Inputs.

MSD600-Output/1 1 Steret Analog Output + 1 Digital AES Output.

(5) DK-Scale PC Program enables users to download new scales from our large library of international standard scales

(6) Only selectable when an output module is present in the unit.