

Test Equipment Depot



1-800-517-8431

99 Washington Street
Melrose, MA 02176
Phone 781-665-1400
Toll Free 1-800-517-8431



Visit us at www.TestEquipmentDepot.com

MODEL 8906

All-in-one thermo-anemometer with integral rotary vane sensor.

- Simultaneous display of air velocity and temperature
- Selectable wind speed units
- Calculate average velocity values
- Calculate air volume by keying in area dimension
- Continuous moving air velocity averaging of measurements for up to 2 hours
- Displays Min/Max/Avg velocity with temperature values
- Multi-point averaging up to 8 points
- High-contrast, 4-digit LCD readout
- RS-232 interface
- Data hold and auto power off
- Includes hard carrying case and batteries



Air Velocity Range: 80 to 5900 fpm;

0.4 to 30 m/s; 0.9 to 68 mph;

1.4 to 108 kph; 0.8 to 58 knots

Resolution: 1 fpm; 0.01 m/s; 0.1 mph;

0.1 kph; 0.1 knot

Accuracy: $\pm 3\%$ of full scale

Temperature Range: 14 to 122°F

(-10 to 50°C)

Resolution: 0.1°F/°C

Accuracy: $\pm 2^\circ\text{F}/\pm 1^\circ\text{C}$

Power Supply: Single 9V battery

Dimensions: 181 x 76 x 45mm

Weight: 210g

**8906
VZRS232BN**

**Thermo-Anemometer
RS-232 Cable**