



Visit us at www.TestEquipmentDepot.com

MODEL AM-4204

Hot wire anemometer is ideal for measuring low air velocities.

- Simultaneously displays air velocity and temperature
- Measure velocities as low as 40 fpm
- Measuring Units: m/s, kph, fpm, mph, knots
- Data hold, Record (Max/Min)
- RS232 serial interface
- Includes telescopic probe w/ 1m cable, 6 x "AAA" batteries and hard carrying case

Air Velocity Range/Resolution:

0.2 to 20.0 m/s/0.1 m/s;
0.7 to 72.0 kph/0.1 kph;
0.5 to 44.7 mph/0.1 mph;
160 to 4930 fpm/1 fpm;
1.0 to 31.1 knots/0.1 knot

Accuracy: $\pm(3\% \text{ rdg.} + 1 \text{ dgt.})$

Temperature Range/Resolution:

32 to 122°F (0 to 50°C)/0.1°F (0.1°C)

Accuracy: $\pm 1.5^\circ\text{F}$ ($\pm 0.8^\circ\text{C}$)

Power Supply: Single 9V battery

Dimensions/Weight: 180 x 72 x 32mm/381g



AM-4204

SW-U801-WIN

UPCB-01

USB-01

Thermo-Anemometer

Software

RS-232 Cable

USB Cable