



Visit us at www.TestEquipmentDepot.com

MODEL C-212

True RMS AC/DC clamp meter.

- True RMS measurements
- Frequency measurement
- 3-3/4 digit LCD with high-speed, 42-segment bargraph
- Max/Min and Data Hold functions
- Peak Hold function
- Diode and continuity test with beeper
- Auto or manual ranging
- Include test leads, soft carrying case & batteries

AC/DC Current Range: 40, 400, 1000A

Resolution: 0.01, 0.1, 1A

Accuracy: AC: $\pm(1.9\% \text{ rdg.} + 5 \text{ dgt.})$;

DC: $\pm(2.5\% \text{ rdg.} + 10 \text{ dgt.})$

Voltage Range: AC: 400, 750V;

DC: 400, 1000V

Resolution: 0.1, 1V AC/DC

Accuracy: AC: $\pm(1.5\% \text{ rdg.} + 5 \text{ dgt.})$;

DC: $\pm(1\% \text{ rdg.} + 2 \text{ dgt.})$

Resistance Range: 400, 4000 Ω

Resolution: 0.1, 1 Ω

Accuracy: $\pm(1\% \text{ rdg.} + 3 \text{ dgt.})$

Frequency Range: 4, 10kHz

Resolution: 1, 10Hz

Accuracy: $\pm(0.1\% + 1 \text{ dgt.})$

Power Supply: Single 9V battery

Jaw Opening: 40mm

Dimensions: 242 x 66 x 36mm (9.5 x 2.6 x 1.4")

Weight: 400g (10 oz)



C-212

True RMS AC/DC Clamp Meter