


Test Equipment Depot



1-800-517-8431

99 Washington Street
Melrose, MA 02176
Phone 781-665-1400
Toll Free 1-800-517-8431



Visit us at www.TestEquipmentDepot.com

MODEL C-380

Detects and pinpoints even small leaks of refrigerant gases.

- Microprocessor control with advanced digital signal processing
- Detects all halogenated refrigerants
- Quickly and accurately mark any leak spot
- Semiconductor gas sensor
- Instantaneous response time
- Audible and visual leak indications
- No user calibration required
- Includes reference leak source and carrying case



Gases Sensed: CFCs: R11, R12, R13; HCFCs: R22, R502, R500; HFCs: R134a, R123, R125, R23, R404A, R407C, R410A and other halogen based compounds

Sensitivity: R22, 134a: Hi 6g/year, L: 30g/year
R404A, 407C, 410A: Hi 8g/year, L: 40g/year

Alarm Settings: Buzzer, Tricolour LED bar indicator

Sensor: Advanced ionization detection

Response Time: Less than 1 second

Warm-up Time: 10 seconds

Power Supply: Single 9V alkaline battery

Battery Life: Approx. 16 hours continuous use

Probe: 390mm (15") flexible stainless probe

Dimensions: 7.3" x 3.4" x 1.4" (18.5 x 8.5 x 3.4 cm)

Weight: 18 oz. (500 g)

C-380

Refrigerant Leak Detector