

MODELS KEW2040/2046R/2055/2056R

- Include test leads, soft carrying case and batteries



MODEL KEW2040.

- Autoranging AC clamp meter and non-contact voltage detector
- 600A current range
- 6000-count display with bargraph
- Data Hold, Min/Max Hold
- Resistance to 60M Ω
- Frequency to 10kHz
- Diode test and continuity buzzer

MODEL KEW2046R.

- Autoranging true RMS AC/ DC clamp meter and non-contact voltage detector
- 600A current range
- 6000-count display with bargraph and backlight
- Data and Peak Hold
- Temperature function
- Resistance to 60M Ω
- Frequency to 10kHz
- Capacitance to 4000 μ F
- Diode test and continuity buzzer

MODEL KEW2055.

- Autoranging AC/DC clamp meter and non-contact voltage detector
- 1000A current range
- 6000-count display with bargraph and backlight
- Data Hold, Min/Max Hold
- Resistance to 60M Ω
- Frequency to 10kHz
- Diode test and continuity buzzer
- Accommodates larger size conductors

MODEL KEW2056R.

- Autoranging true RMS AC/ DC clamp meter and non-contact voltage detector
- 1000A current range
- 6000-count display with bargraph and backlight
- Data and Peak Hold
- Temperature function
- Resistance to 60M Ω
- Frequency to 10kHz
- Capacitance to 4000 μ F
- Diode test and continuity buzzer
- Accommodates larger size conductors

Model	KEW2040	KEW2046R	KEW2055	KEW2056R
AC Current Range	600.0A	600.0A	600.0/1000A	600.0/1000A
Accuracy (50/60Hz)	$\pm 1.5\%$ rdg. ± 5 dgt.	$\pm 2.0\%$ rdg. ± 5 dgt.	$\pm 1.5\%$ rdg. ± 4 dgt.	$\pm 2.0\%$ rdg. ± 5 dgt.
DC Current Range	-	600.0A	600.0/1000A	600.0/1000A
Accuracy	-	$\pm 2.0\%$ rdg. ± 5 dgt.	$\pm 1.5\%$ rdg. ± 5 dgt.	$\pm 1.5\%$ rdg. ± 5 dgt.
AC Voltage Range	6/60/600V	6/60/600V	6/60/600V	6/60/600V
Accuracy	$\pm 1.3\%$ rdg. ± 4 dgt.	$\pm 1.3\%$ rdg. ± 4 dgt.	$\pm 1.3\%$ rdg. ± 4 dgt.	$\pm 1.3\%$ rdg. ± 4 dgt.
DC Voltage Range	600mV/6/60/600V	600mV/6/60/600V	600mV/6/60/600V	600mV/6/60/600V
Accuracy	$\pm 1.0\%$ rdg. ± 3 dgt.	$\pm 1.0\%$ rdg. ± 3 dgt.	$\pm 1.0\%$ rdg. ± 3 dgt.	$\pm 1.0\%$ rdg. ± 3 dgt.
Capacitance	-	40/400nF/4/40/400 μ F	-	40/400nF/4/40/400 μ F
Resistance Range	600 Ω /6/60/600k Ω /6/60M Ω	600 Ω /6/60/600k Ω /6/60M Ω	600 Ω /6/60/600k Ω /6/60M Ω	600 Ω /6/60/600k Ω /6/60M Ω
Accuracy	$\pm 1\%$ rdg. ± 5 dgt.	$\pm 1\%$ rdg. ± 5 dgt.	$\pm 1\%$ rdg. ± 5 dgt.	$\pm 1\%$ rdg. ± 5 dgt.
Frequency Range	9.99/99.99/999.9Hz/9.999kHz	9.99/99.99/999.9Hz/9.999kHz	9.99/99.99/999.9Hz/9.999kHz	9.99/99.99/999.9Hz/9.999kHz
Power Supply	2 x 1.5V "AAA" batteries	2 x 1.5V "AAA" batteries	2 x 1.5V "AAA" batteries	2 x 1.5V "AAA" batteries
Conductor Size	$\varnothing 33$ mm	$\varnothing 33$ mm	$\varnothing 40$ mm	$\varnothing 40$ mm
Dimensions/Weight	243 x 77 x 36mm/300g	243 x 77 x 36mm/300g	254 x 82 x 36mm/310g	254 x 82 x 36mm/310g
Price				