



MODEL LX-105

Simultaneous display of Foot-candles or Lux, plus four lighting types.

- Super large 1.4" (1999 count) LCD display
- Displays % differential from reference point
- "ZERO" re-calibration
- Utilizes precision photo diode colour correction filter
- Cosine and colour corrected measurements
- 4% of full scale accuracy is enhanced by selecting lighting type (Tungsten/Daylight, Fluorescent, Sodium, Mercury)
- Record/Recall Min, MAX and AVG readings
- Data Hold plus Auto shut-off
- Built-in RS-232 serial interface
- Optional Windows® 95/98 compatible software and serial cable
- Optional battery powered datalogger stores over 8000 readings



Range: 200.0/2000/5000 Fc;
2000/20,000/50,000 Lux

Resolution: 1, 10, 100 lux;
0.1, 1, 10 Fc

Accuracy: $\pm 4\%$ of reading

Sampling Rate: 0.4 second

Power Supply: Single 9V battery

Dimensions/Weight:

7.1 x 2.4 x 1.3" (180 x 72 x 33mm)/11.8 oz (335g)

LX-105

DL-9601

SW-U801-WIN

UPCB-02

CA-52A

Light Meter

Data Logger

Software

RS-232 Cable

Soft Carrying Case