

SERIES NGL

The most highly-featured, palm-sized glossmeter available today.

- Available in single 60° or dual 20°/60° angle
- Continuous read feature allows a large surface to be quickly assessed for gloss variations
- Reads matt to mirror surfaces
- Automatic or manual calibration
- Advanced calibration with standard tile check
- Calibrate to any standard
- Automatic calculation of Max, Min, Mean, Std. Deviation and coefficient of variance
- Download results to a PC for full statistical analysis
- Rechargeable ("R") or disposable alkali battery ("D") models



**Test Equipment
Depot**
1-800-517-8431

99 Washington Street
Melrose, MA 02176
Phone 781-665-1400
Toll Free 1-800-517-8431



Visit us at www.TestEquipmentDepot.com

- Simple menu-driven system operated by a 3-button interface
- Easy-to-read angled display

Measuring Range: 20° Angle: 0 to 2000 GU; 60° Angle: 0 to 1000 GU
Repeatability: 0.2 GU
Reproducibility: 0.5 GU
Resolution: 0.1 GU
Measurement Area: 20°: ø 11mm dia.; 60°: 8 x 15mm ellipse
Power Supply: Rechargeable ("R"): NiMH power pack;
Dry Cell ("D"): 4 x "AA" batteries
Battery Life: Rechargeable ("R"): 2200 readings per charge;
Dry Cell ("D"): 3000 readings
Dimensions: 1 x 2 x 4" (25 x 50 x 100mm)
Weight: 12.3 oz (350g)

NGL60D

Glossmeter, Dry Cell, Single 60° Angle

NGL60R

Glossmeter, Rechargeable, Single 60° Angle

NGL20/60D

Glossmeter, Dry Cell, Dual 20°/60° Angles

NGL20/60R

Glossmeter, Rechargeable, Dual 20°/60° Angles