PRESS TOOL



RP 340 PRESS TOOL

Introducing the next generation of Pressing Technology from RIDGID®.

Built to Impress.







BENEFITS

- 30% smaller tool increases maneuverability.*
- 17% lighter tool reduces operator fatigue.*
- 31% longer service interval (up to 42,000 cycles) maximizes uptime.*
- More than 400 presses per charge (with Advanced Lithium 4 Battery).
- Ultimate flexibility with the ability to switch between battery and AC power on the same tool.

Visit us at www.TestEquipmentDepot.com

*Versus RP 330-B

1-800-517-8431

99 Washington Street Melrose, MA 02176 Phone 781-665-1400 Toll Free 1-800-517-8431

SPECIFICATIONS

- Capacity: 1/2" 4" (Copper and Stainless Steel), 1/2" 2" (PEX)
- 270° Barrel/Jaw Swivel
- Hydraulic Ram Output: 7,200 lbs. (32kN)
- Weight: 8.5 lbs. (w/Battery), 9.5 lbs. (w/AC Power Adapter)
- Operating Temperature Range: 15°F to 122°F
- · Approximate Cycle Time: 4 seconds
- LED-light For Continued Operations In No or Low-light Environments
- Longest service interval in the industry: 42,000 Cycles
- Compatible With All Standard Series Pressing Jaws and Attachments From RIDGID®
- For Use With Copper and Stainless Steel Tubing, Steel Pipe, PEX and Cutting Soil Pipe.
- Battery Tool Kit Includes: RP 340 Press Tool, (2) 18V Advanced Lithium 2 Batteries, 120V Advanced Lithium Battery Charger, and Carrying Case
- Corded Tool Kit Includes: RP 340 Press Tool, AC Power Adapter and Carrying Case

ORDERING INFORMATION

| CATALOG NO. | DESCRIPTION | WEIGHT (lb.) (kg) | |
|----------------|---|----------------------|------|
| 43348 | RP 340 Battery Press Tool Kit (No Jaws) | 19 | 8.6 |
| 43353 | RP 340 Battery Press Tool Kit w/ProPress Jaws (1/2"-1") | 31 | 14.1 |
| 43358 | RP 340 Battery Press Tool Kit w/ProPress Jaws (1/2"-2") | 51 | 23.1 |
| 43363 | RP 340 Corded Press Tool Kit (No Jaws) | 16 | 7.3 |
| 43368 | RP 340 Corded Press Tool Kit w/ProPress Jaws (1/2"-1") | 28 | 12.7 |
| 43373 | RP 340 Corded Press Tool Kit w/ProPress Jaws (1/2"-2") | 48 | 21.8 |
| 44483 | RP 340 Press Tool Only | 6 | 2.7 |
| 43378 | RP 340 Press Tool Carrying Case | 8 | 3.6 |
| 44693 | 18V Advanced Lithium 2 Battery | 1 | 0.5 |
| 44698 | 18V Advanced Lithium 4 Battery | 1.5 | 0.7 |
| 43458 | 18V Advanced Lithium Battery Charger | 2 | 0.9 |
| 44798 | 18V Advanced Lithium Battery Charger Replacement Cord | .5 | 0.2 |
| 44468 | 120V AC Power Adapter | 1 | 0.5 |

STANDARD PRESS JAWS AND ACCESSORIES

Standard Jaws for ProPress®

Jaws are designed in conjunction with the Viega® ProPress system to ensure total system compatibility when joining $\frac{1}{2}$ " - 2" copper and stainless steel tubing.



Standard Jaws for PureFlow™

Jaws are designed in conjunction with the Viega PureFlow system. to ensure total system compatibility when joining $\frac{1}{2}$ " – 2" PEX tubing.



Rings for ProPress

Rings for ProPress permit access in tighter spaces and serve as an excellent complement to your RIDGID® jaw sets. The swivel actuator allows a press tool to be placed +/- 90 degrees to the tube being pressed for ½" - 2" connections.



ProPress XL-C® Rings

XL-C Rings and V2 Actuator Jaw include a patented swiveling feature that allows the tool to be placed +/- 90 degrees to the tube being pressed, allowing greater access in tight spaces. Designed in conjunction with the ProPress XL-C fittings, these rings work with RIDGID® Standard Press Tools ensuring total system compatibility with 2½" - 4" connections.



MegaPress® Jaws & Rings

Jaws & Rings join 1/2" to 2" commercially-available Schedule 5-40 Black Iron Pipe when used with RIDGID Standard Press Tools and Viega MegaPress Fittings.



Press Snap™ Soil Pipe Cutter

The Press Snap Soil Pipe Cutter expands the capabilities of RIDGID Standard Press Tools by providing a fast and easy way to cut cast iron soil pipe. Without lengthy lever arms used by traditional soil pipe cutters, improved access is a snap.



MegaPress®, ProPress® and Viega® are registered trademarks of Viega GmbH &Co. PureFlow® and XL-C® are registered trademarks of Viega LLC. RIDGID® and Press Snap™ are registered trademarks of RIDGID, Inc.

