



99 Washington Street
Melrose, MA 02176
Phone 781-665-1400
Toll Free 1-800-517-8431

Visit us at www.TestEquipmentDepot.com



Display Forward, Reflected and VSWR simultaneously

Range from 50µW to 1W

VSWR from 1.04 to 9.99:1

2 GHz to 6 GHz

Diagnose 802.11a,b and g WLAN

SPECIFICATIONS

For WLAN Power Meter

Model No.:	3019
Frequency range:	2 – 6 GHz
Insertion loss:	<0.4dB
Absolute accuracy :	±1dB
Power range indicated:	1µW – 999mW
VSWR indicated:	1.01 – 9.99 : 1
Directivity:	>30dB
Peak Detect of:	<1mS pulse
Auto Power off	1 minute
Power Supply:	3Volt (2 X AAA Alkaline)
Max power consumption:	50 mA
Operating time (no backlight)	20 Hours
Optional Accessories:	SMA to RPSMA adaptors
Belt clip	Option
EMI/RFI	EN55022 /B
Dimensions:	
- Width:	58 mm
- Depth:	23 mm
- Height:	105 mm
Weight incl. Batteries:	approx. 130g
Temperature:	
- Operating	0 to 40°C
- Storage	-20 to 80°C
Colour:	
- Standard	White/Grey