

6800 Series Dissipative Rubber Mats and Runners



The 6800 Series Static Dissipative Rubber Mats and Runners meets ANSI/ ESD S20.20 worksurface required limit (and recommendation of ANSI/ESD S4.1), tested per ANSI/ESD S4.1 and ESD TR53. The 6800 Series mats provide the durability you expect from a dual-layer rubber mat at a very competitive cost. Featuring a smooth finish, the 6800 Series Static Dissipative Rubber Mats and Runners are available in blue/black and gray/black colors, and feature standard sizes in 2 feet, 3 feet and 4 feet widths and 50 feet lengths. In addition, they are also available in 2 feet x 4 feet cut mats in blue/black and gray/black, including snaps.



Properties	Typical Value	Test Method
Material	Nitrile	
Thickness*	0.072" (1.8 mm)	
Color* (Top / Bottom)	Blue / Black Gray / Black	
Hardness (top)	65 Shore A	
*Resistances Surface to Ground (Rtg) Surface to Surface (Rtt)	<10 ⁹ ohms <10 ⁹ ohms	ANSI/ESD S4.1 ANSI/ESD S4.1
Tolerance	Width +/- 0.250" Length +/- 0.250"	

*Color, texture and thickness may vary between lots and mills.

Table Mat Kit Item Numbers

Size	Blue	Gray
2' X 4' (0.6 m X 1.2 m)	6811	6810

Table Mat Kit Includes:
1 Table Mat, size as specified
2 [3034](#) Snap Fasteners (installed)

Runner Item Numbers

Size	Blue	Gray
2' x 50' (0.6 m x 15.2 m)	6841	6840
3' x 50' (0.9 m x 15.2 m)	6861	6860
4' x 50' (1.2 m x 15.2 m)	6871	6870

Mat rolls need to be unrolled before being cut. When rolled, some shrinkage may occur. Please allow time for mat to relax at room temperature 24-48 hours prior to cutting.

Made in China

Specifications and procedures subject to change without notice.

6800 SERIES DISSIPATIVE RUBBER MATS AND RUNNERS

SCS

**DRAWING
NUMBER**
6800

DATE
August
2015