

LanScaperPRO™

Cabling and Network Tester



Key Features

- Detects and reports speed, capability, and location of active Ethernet devices and other connections up to 1 Gbps
- Identifies IEEE 802.3af PoE and legacy Cisco In-Line Power
- Simultaneously pings three addresses at once to verify connectivity to network devices
- Blinks a link indicator to identify hub or switch port and links to Cisco bridge or router ports using Cisco Discovery Protocol
- Tests cabling configuration and verifies connectivity while conducting tests for opens, shorts, miswires, split pairs, and reverses
- Displays length measurement for each pair in feet or meters
- Generates selectable tones on selected pins for use with tone tracers
- Back-lit alphanumeric LCD with icon flags



Applications

- Network testing for port discovery, ping test, and hub flash
- Test PoE to ensure adequate power for powered devices such as VoIP phones
- Identify speed up to 1 Gbps, duplex mode, wiring mode, and polarity of transmit pair on active Ethernet devices
- Conduct single ended and remote cable tests with display of PASS, wiremap, ID, and faults for network cable
- Measure cable length
- Tone and trace cables
- Wiremap network connections with remote identifiers

The LanScaperPRO™ Cabling and Network Tester combines the functions of a high-end cable tester and length measurement device with the capability to identify, monitor, and correct LAN issues associated with physical layer and link conditions in the network.

In network mode testing, the easy-to-use LanScaperPRO enables quick identification at unknown RJ45 jacks for active Ethernet, POTS, token ring, or other devices as well as for presence of devices using power over Ethernet (PoE) at the other end of the jack or cable being tested. LanScaperPRO pings network devices to verify connections and IP addresses, automatically accessing DHCP hosts to obtain network information and can quickly identify hubs, NICs, or auto MDI/MDI-X devices. It also conducts link tests to identify speed and capabilities of network drops.

For cable testing, the LanScaperPRO provides full cabling testing, displaying wire map, ID, and any faults, including shorts, opens, miswires, split pairs, and reverses. The full-featured LanScaperPRO measures cable length and generates tone levels for signal tracing and cable identification on all pairs, a selected pair, or a selected pin.

Physical Specifications

Size (h x w x d)	4.5 x 8.87 x 18.56 cm (1.77 x 3.49 x 7.31 in)
Weight (with batteries)	397 gm (14 oz)
Operating temperature	0 to 50°C (32 to 122°F)
Storage temperature	-30 to 80°C (-20 to 176°F)
Battery life	4 AA alkaline batteries (batteries not included)
Times are for full-capacity batteries used continuously in one of the following modes:	
- Standby	2 yrs
- Cable testing	70 hrs (no backlight) 50 hrs (50% backlight)
- Network testing	7 hrs (no backlight) 6.5 hrs (50% backlight)
Cable types	Network/Ethernet cable, including CAT6, CAT5E, and CAT5
Min cable length for testing split pairs	1 m (3 ft)
Min cable length for single-ended cable test	1.25 m (4 ft)
Length measurement range (CAT5/6)	0 to 457 m (0 to 1,500 ft)

Ordering Information
Description
LanScaperPRO Cabling and Network Tester Kit with remote identifier

- Includes 30.48 cm (1 ft) RJ45 to alligator clips cable (TP40), two 30.48 cm (1 ft) cables with RJ45 connectors (TP55), two 19 cm (7.5 in) RJ12 to RJ12 cables for no-fault connection to RJ11 or RJ45 jacks (TP20), and nylon case

Order Number
NT800
LanScaperPRO Cabling and Network Tester Kit with 8 remote identifiers

- Includes probe (TT100), 30.48 cm (1 ft) RJ45 to alligator clips cable (TP40), two 30.48 cm (1 ft) cables with RJ45 connectors (TP55), two 19 cm (7.5 in) RJ12 to RJ12 cables for no-fault connection to RJ11 or RJ45 jacks (TP20), and nylon case

NT850
Accessories

30.48 cm (1 ft) RJ45 to alligator clips cable	TP40
30.48 cm (1 ft) cable with RJ45 connectors	TP55
19 cm (7.5 in) RJ12 to RJ12 cable for no-fault connection to RJ11 or RJ45 jacks	TP20
Probe, inductive high-sensitivity probe	TT100
Master Wiremapping Kit	KP420
Set of 20 (1-20) RJ45 remote identifiers	TP312
Set of 20 (1-20) RJ11 remote identifiers	TP314
Set of 20 (1-20) two lead remote identifiers	TP315

Warranty

JDSU guarantees that its products will be free of all defects in material and workmanship. This warranty extends for the period of 12 months for test instruments and 3 months for cables from date of manufacture or purchase (proof of purchase required).

All products deemed defective under this warranty will be repaired or replaced at the discretion of JDSU. No further warranties either implied or expressed will apply, nor will JDSU assume responsibility for operation of this device.