

# Agilent E3600-Series Manual Power Supplies

## Data Sheet



- Linear power supply
- Single, dual or triple output
- 10-turn voltage and current controls
- Digital voltage and current meters
- Low noise and excellent regulation

### Affordable, full-featured benchtop power supplies provide excellent performance and flexibility

#### A whole family of low-cost power supplies to meet your needs

The E3600-series of low-cost benchtop power supplies give you the performance of system power supplies without the high price. All E3600 family members give you clean power with dependable regulation and fast transient response. E3600-series single-output models are described on this page. See page 2 for information on dual- and triple-output models.

#### Single-output models

All E3600-series single-output power supplies feature separate digital-panel meters for monitoring voltage and current simultaneously, giving you precise reading and control capability. All models except the E3630A also feature 10-turn potentiometers for accurate adjustment of voltage and current output settings.

With 0.01 percent load and line regulation, these instruments keep the output steady when power line and load changes occur. The low normal-mode noise specification of less than 200 $\mu$ Vrms ensures clean power for precision circuitry.


In all single-output models, either the positive or negative terminal can be connected to ground, providing a positive or negative voltage output. Outputs can also be floated up to 240V from ground.

These instruments also feature adjustable current limits, letting you set the safest current limit without having to short the output.

#### E3610A, E3611A, and E3612A single-output models

These popular 30-watt bench supplies are designed for general laboratory use. The constant-voltage, constant-current output allows operation as either a voltage or current source. The changeover occurs automatically, based on the load. Each of these models has two ranges, allowing more current at a lower voltage. For higher output voltages, supplies can be connected in series.

#### Test Equipment Depot



1-800-517-8431 TestEquipmentDepot.com

99 Washington St.  
Melrose, MA 02176  
FAX 781-665-0780



**Agilent Technologies**

Innovating the HP Way

#### **E3614A, E3615A, E3616A and E3617A models feature overvoltage protection**

These flexible 60-watt, single-range power supplies can be used as either voltage or current sources. When output terminal voltage increases to a preset shut-down level, an overvoltage protection circuit disables the output to protect the device under test (DUT) from damage. The overvoltage protection feature is easily monitored and adjusted from the front panel.

Using remote sensing capability, these instruments automatically compensate for voltage drop in the load leads, so you get accurate voltage at the DUT.

You can combine multiple units in auto-parallel, auto-series and auto-tracking configurations for greater output voltage or current capacity. Front and rear output terminals allow flexible configuration. Output voltage and current can be controlled with external 0- to 10-volt analog voltage or variable resistance.

#### **Multi-output models**

With multiple supplies in a compact unit, the E3620A and E3630A give you excellent performance while saving space on your bench. Both instruments feature tight 0.01 percent line and load regulation and a low normal-mode noise specification of less than 0.35mV to ensure clean power for precision circuitry. With a common-mode current specification of less than 1uA, both multiple-output power supplies minimize power line current injection.

Like the single-output models in the E3600 series, the E3620A and E3630A feature separate digital panel meters so you can monitor voltage and current simultaneously. They also protect your DUT against overload and short-circuit damage. Smooth turn-on and turn-off transitions keep power spikes out of your circuits.

#### **E3620A dual-output power supply**

The 50-watt E3620A dual-output power supply provides two 0 V to 25 Vdc outputs to satisfy most bench requirements. The outputs are completely independent and isolated.

#### **E3630A triple-output power supply**

The 35-watt E3630A triple-output power supply provides three dc outputs: 0 to 6 V with a maximum current of 1 to 2.5A and 0 to 20 V and 0 to -20 V with a maximum current of 0.5A. An autotracking feature lets you use one voltage control to adjust the +20 V and -20 V outputs simultaneously. The outputs track each other to within 1 percent, making it easy to adjust the power supply for circuits requiring balanced voltages.

#### **3-year warranty**

To ensure maximum reliability and long life, all 3600-series power supplies undergo the same rigorous tests as Agilent top-of-the-line power supplies. Each instrument comes with a full 3-year warranty.



## Specifications

	E3610A	E3611A	E3612A	E3614A	E3615A	E3616A	E3617A	E3620A	E3630A
Features	Dual range, 10 turn pots, Constant Voltage (CV), Constant Current (CC) modes.			Adjustable overvoltage protection, voltage & resistance programming, remote sense, rear outputs, ten turn pots, CV, CC modes. Multiple supplies can be connected for tracking or higher power.				Isolated dual outputs, 10 turn pots CV, CL	Tracking, CV, CL (± 20V) CV, CF (+6V)
Number of outputs	1							2	3
Number of output Ranges	2	2	2	1	1	1	1	1	1
DC Output Rating	8V, 3A 15V, 2A	20V, 1.5A 35V, .85A	60V, .5A 120V, 0.25A	8V, 6A	20V, 3A	35V, 1.7A	60V, 1A	25V, 1A 25V, 1A	+6V, 2.5A +20V, 0.5A -20V, 0.5A
Load and Line Regulation	<.01% + 2mV								
Ripple and Noise (20 Hz to 20 MHz)									
Normal mode voltage	<200 μV rms, <2 mV p-p			<200 μV rms, <1 mVpp				<350 μV rms, <1.5 mVp-p	
Normal mode current	<200 μV rms/ 1 mA p-p			<.02%+ 3mA	<.02%+ 1.5mA	<.02%+ 1mA	<.02%+ 0.5mA	—	
Common mode current	not specified							<1 μArms	
Transient Response Time:	<50μsec following change in output current from full load to half load for output to recover to within:								
	10 mV			15 mV					
Meter Accuracy	±0.5% + 2 counts at 25°C ±5°C								
Meter Resolution									
Voltage	10 mV	100 mV	100 mV	10 mV	10 mV (0-20 V), 100 mV (>20V)				10 mA
Current	10 mA	10 mA	1 mA	10 mA	10 mA	1 mA	1 mA	1 mA	10 mA
Isolation	240Vdc								

## Supplemental Characteristics

Control Mode	CV/CC					CV/CL	CV/CL (±20V) CV/CF (+6V)
Temperature Coefficient per °C							
Voltage	< 0.02% + 1mV	< 0.02% + 500µV				<0.02%+1mV	
Current	< 0.02% + 2mA	< .02% + 3mA	< .02% + 1.5 mA	< .02% + 1 mA	< .02% + .5mA	—	
Output Drift							
Voltage	Less than 0.1% + 5mV total drift for 8 hours after an initial warm-up of 30 minutes.						
Current	Less than 0.1% + 10mA total drift for 8 hours after an initial warm-up of 30 minutes.						
Temperature Range							
	0 to 40°C for full rated output. Derate output current 1% per °C between 40°C and 55°C					Derate output current 3.3% per °C	
Cooling	Convection cooling						
Isolation	±240Vdc						
AC Input	100Vac ±10%, 47– 63 Hz (opt. 0E9) 115Vac ±10%, 47– 63 Hz (std) 230Vac ±10%, 47– 63 Hz (opt. 0E3)						
Weight	3.8 kg (8.4 lb.) net, 5.1 kg (11.3 lbs) shipping	5.5 kg (12.1 lb.) net, 6.75 kg (14.9 lbs) shipping					Same as E3610A
Size	91mm H x 213mm W x 319mm D 3.6" H x 8.4" W x 12.6" D	91mm H x 213mm W x 373mm D 3.6" H x 8.4" W x 14.7" D					
Warranty	3 years						
Product Regulation	Certified to CSA 22.2 No. 231; conforms to IEC 1010-1; carries CE mark; complies with CISPR-11, Group 1, Class A						

## Ordering Information

[www.agilent.com](http://www.agilent.com)

### Ordering Information

#### E3600-Series Power Supplies

E3610A 30-Watt Power Supply  
E3611A 30-Watt Power Supply  
E3612A 30-Watt Power Supply  
E3614A 48-Watt Power Supply  
E3615A 60-Watt Power Supply  
E3616A 60-Watt Power Supply  
E3617A 60-Watt Power Supply  
E3620A Dual-output  
Power Supply  
E3630A Triple-output  
Power Supply

#### Accessories included

Operating and service manuals and  
AC power cord

#### Power Options

Opt. 0E3 230 Vac  $\pm 10\%$   
Opt. 0E9 100 Vac  $\pm 10\%$

#### Other Options

Opt. W50 Additional 2-year  
warranty (5-year total)

#### Extra manual sets

E3610A/11A/12A Manual  
(P/N 5959-5304)  
E3614A/15A/16A /17A Manual  
(P/N 5959-5310)  
E3620A Manual  
(P/N E3620-90001)  
E3630A Manual  
(P/N 5959-5329)

#### Rack Mount Kits

**E3610A/11A/12A/30A**  
(P/N 5063-9767)

#### E3614A/15A/16A/17A/20A

To rack mount a single  
instrument (P/N 5063-9240)  
To rack mount instruments side by side  
Lock-link Kit (P/N 5061-9694)  
Flange Kit (P/N 5063-9212)  
To rack mount one or two instruments in a  
sliding support shelf  
Shelf (P/N 5063-9255)  
Slide Kit (P/N 1494-0015)  
For a single instrument, also order filler  
panel (P/N 5002-3999)

### Agilent Technologies' Test and Measurement Support, Services, and Assistance

Agilent Technologies aims to maximize the value you receive, while minimizing your risk and problems. We strive to ensure that you get the test and measurement capabilities you paid for and obtain the support you need. Our extensive support resources and services can help you choose the right Agilent products for your applications and apply them successfully. Every instrument and system we sell has a global warranty. Support is available for at least five years beyond the production life of the product. Two concepts underlay Agilent's overall support policy: "Our Promise" and "Your Advantage."

#### Our Promise

Our Promise means your Agilent test and measurement equipment will meet its advertised performance and functionality. When you are choosing new equipment, we will help you with product information, including realistic performance specifications and practical recommendations from experienced test engineers. When you use Agilent equipment, we can verify that it works properly, help with product operation, and provide basic measurement assistance for the use of specified capabilities, at no extra cost upon request. Many self-help tools are available.

#### Your Advantage

Your Advantage means that Agilent offers a wide range of additional expert test and measurement services, which you can purchase according to your unique technical and business needs. Solve problems efficiently and gain a competitive edge by contracting with us for calibration, extra-cost upgrades, out-of-warranty repairs, and on-site education and training, as well as design, system integration, project management, and other professional services. Experienced Agilent engineers and technicians worldwide can help you maximize your productivity, optimize the return on investment of your Agilent instruments and systems, and obtain dependable measurement accuracy for the life of those products.

By internet, phone, or fax, get assistance with all your test & measurement needs

Online assistance:

[www.agilent.com/find/assist](http://www.agilent.com/find/assist)

#### Phone or Fax

United States:  
(tel) 1 800 452 4844

Canada:  
(tel) 1 877 894 4414  
(fax) (905) 206 4120

Europe:  
(tel) (31 20) 547 2000

Japan:  
(tel) (81) 426 56 7832  
(fax) (81) 426 56 7840

Latin America:  
(tel) (305) 267 4245  
(fax) (305) 267 4286


Australia:  
(tel) 1 800 629 485  
(fax) (61 3) 9272 0749

New Zealand:  
(tel) 0 800 738 378  
(fax) 64 4 495 8950

Asia Pacific:  
(tel) (852) 3197 7777  
(fax) (852) 2506 9284

Data subject to change.  
© Agilent Technologies 2000  
Printed in the U.S.A. 3/00  
5968-9727EN

### Test Equipment Depot



1-800-517-8431 [TestEquipmentDepot.com](http://TestEquipmentDepot.com)

99 Washington St.  
Melrose, MA 02176  
FAX 781-665-0780



**Agilent Technologies**

Innovating the HP Way